# Technisches Datenblatt

**Y.06 6653**

23/11/2026

INSTALLATION FÜR PULVERLACKSPRITZEN

# Nippon Static Auto powdercoat line

Marke: Nippon Static · Typ: Auto powdercoat line












## TECHNISCHE DATEN

Spezifikationen auf Anfrage.

## BESCHREIBUNG

Consists of:

1 - Powder coat booth equiped with 4 automatic pistols. The control cabinet allows each pistol to be regulated in terms of powder & voltage (0-100kV - negative tension). Voltage and excess current can be monitored on a display, the current can be lowered which is usefull in case a second coating is needed.

2 - A gaspowered oven (indirect heating), dimensions: length 10 000 x width 3000 x height 3700 + 750 mm - entry dimensions: 500 x 2500 mm or 2500 x 2500 mm if entrygap is changed

3 - 112 meter chain conveyor line type CT 300

4 - recuperation system: dual cyclone - auto recovery system - filter and fan


## KONTAKT

**Dam-Apt BV**

De Tonne 77 · 9800 Deinze · Belgien

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · USt-IdNr. BE 0405.595.996


Scannen für das Online-Datenblatt

PREIS

## Preis auf Anfrage

Angebot anfragen


**KONTAKT**

**Dam-Apt BV**

De Tonne 77 · 9800 Deinze · Belgien

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · USt-IdNr. BE 0405.595.996


Scannen für das Online-Datenblatt