APT INTERNATIONAL

Technisches Datenblatt

Z.10g 4265

23/11/2026

PVC EXTRUSIONSTRASSE

Davis-Standard 45 IN 45 HT

Marke: Davis-Standard · Typ: 45 IN 45 HT











PVC EXTRUSIONSTRASSE

Bedrückte profiel PVC panelen	**ABS, EPDM & PE**	Max kapzität	**329 kW**
Max paneelweite	**1650 mm**		

BESCHREIBUNG

Sold in one lot with Extrusion line Z10a 4251 (Johnson-Spaten) Extrusionlines with Co-extrusion for production of ABS, EPDM & PE plates Co-extrusion of plates with different top & bottom layer Max Extrusion width: 1650 mm, thickness: 15 mm Total production in 1 year (2 lines) = 1.700.000kgs Co-extrusion Line Davis-Standard: 1) Main extruder Typ 45 IN 45 HT Motor: 329 kW 2) 2 x Co-extruders 15-IN-20 Cap: Motor: 3) Extrusion Head width 2000 mm 4) Roll + Inclination Roll with Cooler (Roll Ø 405 mm) Width 1650mm Several Relief rolls with the machine 5) Flying Shear Haco 2000mm wide Including Dryer Somos, mixing Silos, Suction Sytem for basic products

PREIS

Preis auf Anfrage

Angebot anfragen

KONTAKT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgien

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · USt-IdNr. BE 0405.595.996

Scannen für das Online-Datenblatt