Technical datasheet

B.04 11090

23/11/2026

BED MILLING MACHINE WITH MOVING COLUMN & CNC

Anayak / Correa X: 4300 – Y: 1500 – Z: 2500 mm CNC

Brand: Anayak · Type: / Correa X: 4300 - Y: 1500 - Z: 2500 mm CNC











BED MILLING MACHINE WITH MOVING COLUMN & CNC

Longitudinal travel X-axe	**4300 mm**	Crosstravel Y -axe	**1500 mm**
Travel Z-axe (Height)	**2500 mm**	Table size	**2000 x 1600 mm**
Power on spindle	**22/30 kW**	Type of millinghead	**multi-angular**
Admission in millingheadspindle (ISO)	**ISO 50**	Max speedrange	**3000 rpm**
Control	**Heidenhain iTNC 530**	Weight	**46 ton**

BORERS WITH TRAVELLING COLUMN, FLOOR TYPE

Longitudinal travel X-axis	**4300 mm**	Cross traverse Y-axis (table/column)	**1500 mm**
Vertical traverse Z-axis	**2500 mm**	Spindle traverse W-axis	**1500 mm**
Milling spindle taper (ISO)	**ISO 50**	Spindle power	**22/30 kW**
Spindle speed range	**3000 rpm**	Digital read-out (1) CNC(2)	**Heidenhain iTNC 530**
Rotary table dimensions	**2000 x 1600 mm**	Weight	**46 ton**
Type (1x180°)	**multi-angular**		

DESCRIPTION

Type: HVM 5000 P-MG

Automatic multi-angular millinghead = automatic B- & A-axis

High pressure cooling through spindle

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet

Toolchanger with 30 positions

Movement of the table: 1500 mm

Chip conveyor

The table is currently sitting on top of a concrete foundation of 300 mm high.

No foundation required!

PRICE

Price on request

Request a quote

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet