APT INTERNATIONAL

Technical datasheet

B.04 16238

24/11/2026

BED MILLING MACHINE WITH MOVING COLUMN & CNC

Fanuc Milling Robot X: 10 500 / Y: 3045 / Z: 3500 mm CNC

Brand: Fanuc Milling Robot · Type: X: 10 500 / Y: 3045 / Z: 3500 mm CNC











TECHNICAL SPECIFICATIONS

Specifications on request.

DESCRIPTION

Fanuc 6-axis robotic milling center for aluminum and steel

Fanuc R-2000-B/165F

CNC: R-30iA CONTROLLER

X-movement of the robot on track: 10,500 mm

Extended robot arm reach (left and right): 3045 mm

> maximum workpiece length if it is a profile: 15 meters

> max. workpiece size without extended arm reach: 10,500 x 3045 mm

> max. workpiece height: 3500 mm

> max weight which can be attached to the robot: 165 kg

> weight of only the robot: 1200 kg

Toolchanger mounted on the track with 13 tool positions:

- 12 live tools - ISO BT 40

- 1 measuring probe

Milling head:

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet

TMA6 17/2

Speed: 1 > 12,000 rpm

ISO 40 - 11 kW

Weight: 45 kg

There are many configurations possible, depending on the type of workpiece. Currently there are two separate work areas, but you can change this to one work area (for a large workpiece) or split it into multiple separate work areas for smaller workpieces.

PRICE

Price on request

Request a quote

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet