APT INTERNATIONAL

Technical datasheet

U.10 1861

23/11/2026

PLASTIC INJECTION MOLDING & INDUCTION FURNACES

Meiki M 350-1270 DM

Brand: Meiki · Type: M 350-1270 DM









MODEL / APPLICATION				M-350-DM		
Hopper capacity			L	140		
Screw speed	Fast	60HZ	rpm	0 - 240		
	Fast	50HZ	rpm			
	Slow	60HZ	rpm			
	Slow	50HZ	rpm	0 - 120		
Heater capacity			KW	19.55		
Cooling fan capacity		60HZ	W	110×3		
		50HZ	W			
Screw diameter			mm	65	70	75
Plasticizing capacity		60HZ	kg/hr			
		50HZ	kg/hr	140	200	220
Injection pressure			kg/cm	1790	1543	1344
Injection capacity			cm³	1160	1347	1546
			gr	1097	1270	1460
			oz	38.7	44.8	51.5
Injection rate		60HZ	cc/sec			
		50HZ	cc/sec	292	338	388
Injection cyl. stroke			mm	350		
Injection speed		60HZ	cm/sec			
		50HZ	cm/sec	8.8		
Injection ram dia			mm	185×85 (2)		

PLASTIC INJECTION MOLDING & INDUCTION FURNACES

Distance between uprights	**750 mm**	Max distance between : base -- open	**300-800 mm**
Operating pressure	**350 T /1543 bar**		

DESCRIPTION

Plastic-injection / Plate 1070 mm Injection weight 1270 gr screw Ø 70 mm Seprofluxfeeding + robot IDEM U10 1860

PRICE

Price on request

Request a quote

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet