Technical datasheet

M.04 8937

23/11/2026

OPEN GAP STRAIGHTENING PRESSES

LVD 400 ton

Brand: LVD · Type: 400 ton











H-FRAME PRESSES

Capacity	**400 ton**	Max ram adjustment	**1550 mm**
Drawningspeed	**30 mm/sec**	Workingspeed	**2 mm/sec**
Returningspeed	**50 mm/sec**	Passage between uprights	**3900 mm**
Max distance between table - ram	**1550 mm**	Dimensions of the table	**7000 x 3200 mm**
Electric motor (power)	**11 kW**	Length	**8500 mm**
Depth	**5900 mm**	Height	**4900 mm**
Weight	**85 ton**		

OPEN GAP STRAIGHTENING PRESSES

Capacity	**400 ton**	Max ram adjustement	**1550 mm**
Drawingspeed	**30 mm/sec**	Workingspeed	**2 mm/sec**
Returningspeed	**50 mm/sec**	Max distance between table -- ram	**1550 mm**
Dimensions of the table	**7000 x 3200 mm**	Electric motor (power)	**11 kW**
Length	**8500 mm**	Depth	**5900 mm**

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet

Height	**4900 mm**	Weight	**85 ton**

HORIZONTAL PRESSES

Capacity	**400 ton**	Max ram adjustment	**1550 mm**
High speed displacement	**30 mm/sec**	Working speed	**2 mm/sec**
Returning speed	**50 mm/sec**	Passage between uprights	**3900 mm**
Max distance between table -- ram	**1550 mm**	Table area	**7000 x 3200 mm**
Electric motor (power)	**11 kW**	Length	**8500 mm**
Depth	**5900 mm**	Height	**4900 mm**
Weight	**85 ton**		

DESCRIPTION

Portal straightening press 400 tons

Model: GANTRY-400T >> For straightening shafts, cast steel products, rolled products, free-die forgings, flat steel, and also for pressing in and out bearings, bushings, shrink rings, etc. 14 individual counter pressure cylinders in the table - 3 ton cap per cylinder - 100 mm slug per cylinder

- Pressure 300 kg/cm²
- Clearance between the uprights: 3990 mm

Operating speed – at max. pressure: 2 mm/sec

Return speed: 50 mm/sec

Shutter speed: 30 mm/sec

PRICE

Price on request

Request a quote

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet