APT INTERNATIONAL

# Technical datasheet

**O.01 8543**

23/11/2026

HYDRAULIC PRESS BRAKES

# Beyeler Bystronic PR10 1400 ton x 14 500 mm CNC

Brand: Beyeler Bystronic PR10 · Type: 1400 ton x 14 500 mm CNC













## HYDRAULIC PRESS BRAKES

| | | | |
|---|---|---|---|
| Capacity | **1400 ton x 14500 mm** | Control | **Cybelec DNC 906 PS** |
| Passage between uprights | **11 000 mm** | Max stroke | **900 mm** |
| Max distance between table -- ram | **1500 mm** | Depth of throat | **1280 mm** |
| Table width | **1000 mm** | Drop speed | **80 mm/sec** |
| Working speed | **8 mm/sec** | Returning speed | **80 mm/sec** |
| Electric motor (power) | **110 kW** | Length | **15650 mm** |
| Depth | **4650 mm** | Height | **6300 mm** |
| Weight | **348 ton** | | |

## DESCRIPTION

8 axes: Y1 - Y2 - Z1 - Z2 - Z3 - X1 - X2 - X3 adjustable opening for bending die servo hydraulic cnc machine hydraulic bombation 2 front tables (movable on rails) 3 independant backgauges (R-axis is manually adjustable) conical bending

bending examples: - 35 mm thickness at 6 meter length - 22 mm thickness at 10 meter length - 20 mm thickness at 12 meter length - 15 mm thickness at 14,5 meter length ---------- 8 управляемых осей: Y1 - Y2 - Z1 - Z2 - R1 - R2 - X1 - X2 Раздвижной стол для различных матриц Гидравлический компенсатор прогиба


## CONTACT

**Dam-Apt BV**

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996


Scan for the online datasheet

Примеры гибки: - Толщина 35 мм при длине 6 метров - Толщина 22 мм при длине 10 метров - Толщина 20 мм при длине 12 метров - Толщина 15 мм при длине 14,5 метров

PRICE

**Price on request**

Request a quote


**CONTACT**

**Dam-Apt BV**

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996


Scan for the online datasheet