Technical datasheet

O.19 1003 *03

23/11/2026

STAMPING & PUNCHING PRESS THIN METALSHEET

Trumph 500 R-1600 tru

Brand: Trumph · Type: 500 R-1600 tru











STAMPING & PUNCHING PRESS THIN METALSHEET

Punching pressure	**220 kN**	Max sheet thickness by punching + nibbling	**8 mm**
Max punching dia	**76,2 mm**	Max weight workpiece	**230 kg**
Working range on cross-side (X-axes)	**3085 mm**	Working range along (Y-axes)	**1650 mm**
Positioning speed along X-axes	**90 m/min**	Positioning speed along Y-axes	**60 m/min**
Control	**Trumag.CC220S**	Toolchanger	**Automatic**
Number of toolpositioners	**18**	Changingtime	**1,5 -- 5 sec**

DESCRIPTION

First time use : 1996 -- Rotation axle 360° continue -- Motor axes X,Y & C without maintenance -- punching axle : hydraulic + TRUMALIFT sheetmaster : automatical loading & unloading + TRUMAGRIP 500 :

PRICE

Price on request

Request a quote

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet