APT INTERNATIONAL

Technical datasheet

O.19 0728 *03

23/11/2026

STAMPING & PUNCHING PRESS THIN METALSHEET

Trumph TC 260 Trumatic

Brand: Trumph · Type: TC 260 Trumatic











STAMPING & PUNCHING PRESS THIN METALSHEET

Punching pressure	**250 kN**	Max sheet thickness by punching + nibbling	**6,4 mm - 1/4**
Max punching dia	**76,2 mm**	Max weight workpiece	**100 kg**
Working range on cross-side (X-axes)	**2600 mm**	Working range along (Y-axes)	**1300 mm**
Positioning speed along X-axes	**50m/min**	Positioning speed along Y-axes	**40m/min**
Control	**CNC**	Toolchanger	**Automatic**
Number of toolpositioners	**10**	Changingtime	**7 sec**
Power needed	**14 kVA**	Tension	**380 V**
Weight	**8000 kg**		

DESCRIPTION

sr 050692

PRICE

Price on request

Request a quote

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet