APT INTERNATIONAL

Technical datasheet

B.01 4772 *08

23/11/2026

UNIVERSAL MILLING MACHINES & CNC

Deckel-Maho DMG DMC 100 V Hi-Dyn

Brand: Deckel-Maho DMG · Type: DMC 100 V Hi-Dyn











UNIVERSAL MILLING MACHINES & CNC

Max longitudinal travel X-axe	**1000 mm**	Max cross-travel Y-axe	**800 mm**
Max travel Z-axe	**500 mm**	Max height workpiece	**700 mm**
Power on spindle	**15 kW**	Admission in millinghead	**HSK-A 63**
Spindlespeeds	**max 18000 rpm**	Table size	**1250 x 800 mm**
Control	**Heidenhain TNC 426**	Power needed	**3 x 380 V**
Length	**3100 mm**	Depth	**2400 mm**
Height	**2600 mm**	Weight	**9100 kg**
Coolant pump	**yes**	Turret	**yes**
Number of tools	**30**		

DESCRIPTION

Splash guard with Top Top Splash guard cabin closed Direct path measuring system External air blast cooling External air blast cooling through 2 pipes, selectable by M-function or softkey (coolant or air selectable) Internal coolant supply through the centre of spindle form A-D, (23 l/min at 40 bar / 6.1 gal/min at 580 psi), total tank capacity 940 l / 248.3 gal Spray gun with bed flushing Rotoclear inspection window Oil mist separator Machine working space extraction Manual control panel Chip conveyor Ethernet Interface TNC 3 x 380 V - 90A

PRICE

Price on request

Request a quote

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgium

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Scan for the online datasheet