# Ficha técnica

**O.24 0999 *06**

23/11/2026

REPUJADORAS

# Leifeld APED 300

Marca: Leifeld · Tipo: APED 300





**For Sale**

Automatic Spinning, Flow Turning and Necking-in Machine

LIEFELD APED 350

Leifeld's many years of experience in the manufacture of automatic machinery are incorporated in the design of this newly developed lathe. Special importance has been attached to the lathe being able to cope with the heavy demands of series production on an industrial basis and to guarantee high repeat accuracy of the machine settings in the interest of short setting-up times.
Special features of the lathe include:
The cross slide supported over its entire length at the rear of the lathe; longitudinal feed by hydraulic cylinder with a very accu-rate, viscosity-independent, infinitely variable speed control, infinitely variable contact pres-sure for easy matching to various materials with their different properties; the bed block for the slide vibration-free and extending down to the floor; the numerous attachments available for the lathe, where equipment for special purposes can be developed by the user if required; with mobile control console or fixed control panel.

Technical Data:

| | |
|---|---|
| Center height | mm 350 |
| Distance between centers | mm 900 |
| Bed length | mm 2200 |
| Tool mounting using centering flange | DIN 55022, Size 8 or 6 |
| Speeds of main spindle infinitely variable | rpm 280-2300 |
| Drive rating | kW 4 |
| Drive rating of hydraulic unit | kW 7,5 |
| Tailstock sleeve travel | mm 500 |
| Ejektor stroke | mm 200 |
| Longitudinal travel of slide | mm 300/400 |
| Transverse travel of slide | mm 275 |
| Longitudinal thrust | kN 14 |
| Transverse thrust | kN 18 |
| Approx. net weight | kg 3400 |

## REPUJADORAS

| | | | |
|---|---|---|---|
| Centerheight | **350 mm** | Distance between centers | **900 mm** |
| Worklength | **2200 mm** | Longitudinal travel X-axes | **400 mm** |
| Cross travel Y-axes | **275 mm** | Tail-stock travel | **500 mm** |
| Ejection-pin travel | **200 mm** | Speeds | **A 200-600 rpm** |
| Admission in spindlenose | **M 60, DIN 800** | Voltage | **380 V** |

## DESCRIPCIÓN

sr 29512-19/10 -- Snelheden : Positie B 585 - 1800 rpm

PRECIO

**Precio bajo consulta**

**Solicitar presupuesto**


## CONTACTO

**Dam-Apt BV**

De Tonne 77 · 9800 Deinze · Bélgica

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · IVA BE 0405.595.996


Escanee para la ficha en línea