APT INTERNATIONAL

Fiche technique

Y.06 6653

23/11/2026

INSTALLATION POUR PEINTURE EN POUDRE

Nippon Static Auto powdercoat line

Marque: Nippon Static · Type: Auto powdercoat line











SPÉCIFICATIONS TECHNIQUES

Spécifications sur demande.

DESCRIPTION

Consists of:

1 - Powder coat booth equiped with 4 automatic pistols. The control cabinet allows each pistol to be regulated in terms of powder & voltage (0-100kV - negative tension). Voltage and excess current can be monitored on a display, the current can be lowered which is usefull in case a second coating is needed.

2 - A gaspowered oven (indirect heating), dimensions: length 10 000 x width 3000 x height 3700 + 750 mm - entry dimensions: 500 x 2500 mm or 2500 x 2500 mm if entrygap is changed

3 - 112 meter chain conveyor line type CT 300

4 - recuperation system: dual cyclone - auto recovery system - filter and fan

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgique

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · TVA BE 0405.595.996

Scannez pour la fiche en ligne

PRIX

Prix sur demande

Demander un devis

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgique

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · TVA BE 0405.595.996

Scannez pour la fiche en ligne