APT INTERNATIONAL

Fiche technique

T.10 8286

23/11/2026

TRANSFORMATEURS (DE SOUDAGE)


SAF Optipuls 350 amp

Marque: SAF Optipuls · Type: 350 amp









		OPTIPULS 300i W	OPTIPULS 500i W
Primary		400 V - 50/60 Hz	
	Three-phase primary voltage		
	Primary consumption at max current	28 A	44 A
Secondary		96.8 V	57 V
	No load voltage		
	Adjustment range	10 A - 350 A	10 A - 500 A
	Duty cycle at 40° C at 60%	350 A	450 A
	at 100%	300 A	400 A
Wires usable	Steel/SS	0.8 - 1.6 mm	
	Aluminium	1.0 - 1.6 mm	
	Flux-cored wire	1.0 - 2.4 mm	
Welding cycle		25 - 45	
Mode		• synergic or manual • adjustment by set-up of the cycle parameters • flux cored wire selection	
Dimensional characteristics:		1090 x 610 x 970	
	Dimensions (L x l x h)		
	Weight	96 kg (water) 91 kg (air)	107 kg (with cooling unit)
DV44i wire feeder		4	
	Number of rollers		
	Wire feed rate	0 to 20 m/min	
Protection		IP 23	
Standards		EN 60974-1	

TRANSFORMATEURS (DE SOUDAGE)

Semi-autom(1)Baguette(2)AC-DC tig(3)	**mig mag**	Puissance	**350 amp**

DESCRIPTION

welding torch included

PRIX

Prix sur demande

Demander un devis

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgique

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · TVA BE 0405.595.996

Scannez pour la fiche en ligne