APT INTERNATIONAL

Scheda tecnica

O.06 12489

28/11/2026

CALANDRE

Schafer SVRM 3200 x 140 mm


Marca: Schafer · Tipo: SVRM 3200 x 140 mm











CALANDRE

Numero di rulli	**4 rolls**	Capacità di laminazione a freddo	**3000 x 70 mm**
Capacità di laminazione a caldo	**3200 x 140 mm**	Diametro del rullo superiore	**650 mm**
Potenza motore	**180 HP**	Peso	**140 ton**
Possibilità di tastatura	**yes**		

DESCRIZIONE

4 roll bending roll >> can also be used for hot rolling & also appropriate for heavy duty conical rolling

The 3 lower rolls can all tilt independently on both sides, this is a unique and rare feature which allows for heavy duty conical rolling. Usually for normal conical rolling only the side rolls can tilt.

3 lower rolls are mechanically driven with driveshafts = no slip possible of workpiece
Hydrostatic motors (can be independently controlled) connected to gearbox
Hydraulic upper & lower movement of rolls and support bearing
Diameter of upper- & lower roll: 650 mm
Max distance between upper- & lower roll: 300 mm
Diameter of side rolls: 500 mm
Treated rolls 42CrMo4
Smallest diameter of workpiece at 60 mm thickness (cold) = 720 mm
Working speed: 1 > 8 m/min

CONTATTI

Dam-Apt BV
De Tonne 77 · 9800 Deinze · Belgio
Tel: +32 (0)9 386 15 71 · info@aptint.com
www.aptint.com · P. IVA BE 0405.595.996

Scansiona per la scheda online

600 ton clamping force

350 ton rolling force

PREZZO

Prezzo su richiesta

Richiedi un preventivo

CONTATTI

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgio

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · P. IVA BE 0405.595.996

Scansiona per la scheda online