APT INTERNATIONAL

# Scheda tecnica

**O.24 0999 *06**

23/11/2026

FILATOI

# Leifeld APED 300

Marca: Leifeld · Tipo: APED 300





**For Sale**

Automatic Spinning, Flow Turning and Necking-in Machine

LIEFELD APED 350

Leifeld's many years of experience in the manufacture of automatic machinery are incorporated in the design of this newly developed lathe. Special importance has been attached to the lathe being able to cope with the heavy demands of series production on an industrial basis and to guarantee high repeat accuracy of the machine settings in the interest of short setting-up times.
Special features of the lathe include:
The cross slide supported over its entire length at the rear of the lathe; longitudinal feed by hydraulic cylinder with a very accu-rate, viscosity-independent, infinitely variable speed control, infinitely variable contact pres-sure for easy matching to various materials with their different properties; the bed block for the slide vibration-free and extending down to the floor; the numerous attachments available for the lathe, where equipment for special purposes can be developed by the user if required; with mobile control console or fixed control panel.

Technical Data:

| | |
|---|---|
| Center height | mm 350 |
| Distance between centers | mm 900 |
| Bed length | mm 2200 |
| Tool mounting using centering flange | DIN 55022, Size 8 or 6 |
| Speeds of main spindle infinitely variable | rpm 280-2300 |
| Drive rating | kW 4 |
| Drive rating of hydraulic unit | kW 7,5 |
| Tailstock sleeve travel | mm 500 |
| Ejektor stroke | mm 200 |
| Longitudinal travel of slide | mm 3004400 |
| Transverse travel of slide | mm 275 |
| Longitudinal thrust | kN 14 |
| Transverse thrust | kN 18 |
| Approx. net weight | kg 3400 |

## FILATOI

| | | | |
|---|---|---|---|
| Altezza del centro | **350 mm** | Distanza tra centri | **900 mm** |
| Lunghezza banco | **2200 mm** | corsa longitudinale asse X | **400 mm** |
| Traslazione trasversale asse Y | **275 mm** | Contropunta a corsa | **500 mm** |
| Corsa espulsore | **200 mm** | Velocità | **A 200-600 rpm** |
| Attacco mandrino | **M 60, DIN 800** | Tensione | **380 V** |

## DESCRIZIONE

sr 29512-19/10 -- Snelheden : Positie B 585 - 1800 rpm

PREZZO

**Prezzo su richiesta**

**Richiedi un preventivo**


## CONTATTI

**Dam-Apt BV**

De Tonne 77 · 9800 Deinze · Belgio

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · P. IVA BE 0405.595.996


Scansiona per la scheda online