APT INTERNATIONAL

Scheda tecnica

Z.02 5528


23/11/2026

SVOLGITORE + / O LINEE DI PROFILATURA

Extrusion/production line XPS Styrofoam/Styrodur insulation panels

Marca: Extrusion/production line · Tipo: XPS Styrofoam/Styrodur insulation panels











INDUSTRIE/IMPIANTI E STABILIMENTI COMPLETI IN VENDITA

Vedi	**O27 5528 / U10 5528 / Z10 5528**

SVOLGITORE + / O LINEE DI PROFILATURA

Modalità di lavoro	**EXTRUSION - XPS**	Spessore x larghezza del materiale	**120 x 800 mm**
Velocità di produzione	**800 kg/h**	Potenza totale necessaria	**300 kW**
Lunghezza x larghezza totale	**1200 x 800 mm**	DISPOSITIVO DI TAGLIO o DI SEZIONAMENTO	**Yes**
IMPIANTO DI IMPILAMENTO	**Yes**		

DESCRIZIONE

Complete automatic production line for Styrofoam / Styrodur panels -> production of XPS-panels - Mixing and loading system - 2 Extruders - Static Mixter - Filter changer - Die - one set - Calibrating system - Cutting and milling systems - Overturn cooling platform - Water cooling unit - Automatic packing machine - Oven house - Automatic transportion bench + RECYCLING SYSTEM

Work mode EXTRUSION - XPS **Material thickness x width** 120 x 800 mm **Production speed** 800 kg/h **Total rated power** 300 kW **Length x width over all** 1200 x 800 mm **CUTTING DEVICE** Yes **Stacking device** Yes

Capacty 25m³/h XPS Styrofoam/Styrodur insulation panels

CONTATTI

Dam-Apt BV
De Tonne 77 · 9800 Deinze · Belgio
Tel: +32 (0)9 386 15 71 · info@aptint.com
www.aptint.com · P. IVA BE 0405.595.996

Scansiona per la scheda online

PREZZO

Prezzo su richiesta

Richiedi un preventivo

CONTATTI

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgio

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · P. IVA BE 0405.595.996

Scansiona per la scheda online