APT INTERNATIONAL

Technische fiche

T.10 8294

23/11/2026

LASPOSTEN & LASTRANSFORMATOREN

SAF Optipuls 350 amp

Merk: SAF Optipuls · Type: 350 amp





	OPTIPULS 300 W	OPTIPULS 500 W
Primary	400 V - 50/60 Hz	
Three-phase primary voltage		
Primary consumption at max current	28 A	44 A
Secondary		
No load voltage	66.8 V	57 V
Adjustment range	10 A - 350 A	10 A - 500 A
Duty cycle at 40° C at 60%	350 A	450 A
at 100%	300 A	400 A
Wires usable Steel/SS	0.8 - 1.6 mm	
Aluminum	1.0 - 1.6 mm	
Flux-cored wire	1.0 - 2.4 mm	
Welding cycle	20 - 45	
Mode	• synergic or manual • adjustment by set-up of the cycle parameters • flux cored-wire selection	
Dimensional characteristics: Dimensions (L x l x h)	1090 x 610 x 970	
Weight	96 kg (water) 91 kg (air)	107 kg (with cooling unit)
DV44 wire feeder Number of rollers	4	
Wire feed rate	0 to 20 m/min	
Protection	IP 23	
Standards	EN 60974-1	



LASPOSTEN & LASTRANSFORMATOREN

Halfautomaat (1)Elektr.(2) AC-DC tig(3)	**mig mag**	Vermogen	**350 amp**

BESCHRIJVING

welding torch included

PRIJS

Prijs op aanvraag

Vraag een offerte aan

CONTACT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · België

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · BTW BE 0405.595.996

Scan voor de online fiche