Karta techniczna

Y.06 6653

23/11/2026

INSTALACJA DO POKRYWANIA PROSZKOWEGO

Nippon Static Auto powdercoat line

Marka: Nippon Static · Typ: Auto powdercoat line











SPECYFIKACJA TECHNICZNA

Specyfikacja na życzenie.

OPIS

Consists of:

1 - Powder coat booth equiped with 4 automatic pistols. The control cabinet allows each pistol to be regulated in terms of powder & voltage (0-100kV - negative tension). Voltage and excess current can be monitored on a display, the current can be lowered which is usefull in case a second coating is needed.

2 - A gaspowered oven (indirect heating), dimensions: length 10 000 x width 3000 x height 3700 + 750 mm - entry dimensions: 500 x 2500 mm or 2500 x 2500 mm if entrygap is changed

3 - 112 meter chain conveyor line type CT 300

4 - recuperation system: dual cyclone - auto recovery system - filter and fan

KONTAKT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgia

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Zeskanuj, aby zobaczyć kartę online

CENA

Cena na zapytanie

Poproś o ofertę

KONTAKT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgia

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Zeskanuj, aby zobaczyć kartę online