APT INTERNATIONAL

Karta techniczna

Z.10a 4252

23/11/2026

LINIA WYTŁACZANIA PCV

Davis-Standard 45 IN 45 HT

Marka: Davis-Standard · Typ: 45 IN 45 HT











LINIA WYTŁACZANIA PCV

Plastic grinding mill	**NO**	Capacity	**329 kW**
2 extrusionstreets for blades	**YES**	Max wide	**1650 mm**
Dosing-plant	**Yes**	Automatic shear	**Yes - Haco 2000mm**
Evacuation of product	**Yes**		

OPIS

Sold in one lot with Extrusion Line Z10a 4251 (Johnson-Spaten) Extrusionlines with Co-extrusion for production of ABS, EPDM & PE plates--- Co-extrusion of plates with different top & bottom layer---- Max Extrusion width: 1650 mm, thickness: 15 mm---- Total production in 1 year (2 lines) = 1.700.000kgs---- Davis-Standard: 1) Main extruder Typ 45 IN 45 HT Motor: 187.5 kW @ 380V Cap: 15000W ----- 2) 2 x Co-extruders 15-IN-20 Cap: Motor: ----- 3) Extrusion Head width 2000 mm ----- 4) Roll + Inclination Roll with Cooler (Roll Ø 405 mm) Width 1650mm Several Relief rolls with the machine ----- 5) Flying Shear Haco 2000mm wide ----- Including Dryer Somos, mixing Silos, Suction Sytem for basic products

CENA

Cena na zapytanie

Poproś o ofertę

KONTAKT

Dam-Apt BV

De Tonne 77 · 9800 Deinze · Belgia

Tel: +32 (0)9 386 15 71 · info@aptint.com

www.aptint.com · VAT BE 0405.595.996

Zeskanuj, aby zobaczyć kartę online